PROVINCE OF BRITISH COLUMBIA

ORDER OF THE LIEUTENANT GOVERNOR IN COUNCIL

·			
Order in Council No	413	, Approved and Ordered	JN - 6 2008
Executive Council C	hambers, Victoria	A bush 6 a - a	Lieutenant Governor Administration
On the recomm	nendation of the und		nor, by and with the advice and consent of
		in the Schedule to this order.	the Commercial Transport Regulations,
Minister of Transport	Ortation .	Pre	DMULL Legding Member of the Executive Council
Authority under which		for administrative purposes only and is not po	art of the Order.)
Act and section:-		sport Act, R.S.B.C. 1996, c. 58, s.	11
Other (specify):-	OIC 27/78		
May 9, 2	2008		R/453/2008/14

SCHEDULE

- 1 Section 7.06 of the Commercial Transport Regulations, B.C. Reg. 30/78, is amended
 - (a) in paragraph (b) by striking out "20 cm on each side" and substituting "30 cm on each side", and
 - (b) by repealing paragraph (c) and substituting the following:
 - (c) auxiliary equipment or devices that are not designed or used to carry cargo and do not extend more than 10 cm on each side beyond the total width of vehicle and load otherwise permitted by this section, including, but not limited to, anti-splash and spray devices, load securement devices, ladders, glad hands, air connectors, electrical connectors, hydraulic connectors, clearance lamps and dangerous goods placards;

2 Section 7.07 (1) is amended

- (a) in paragraph (a) by striking out "after August 31, 1988, and before January 1 1994," and substituting "after August 31, 1988 and before January 1, 1994 and is not equipped with super single tires,",
- (b) in paragraph (a) by striking out "and" at the end of subparagraph (ii), and
- (c) by repealing paragraph (b) and substituting the following:
 - (b) if the semi-trailer, pony trailer or full trailer was manufactured after December 31, 1993 and is not equipped with super single tires, the distance across the outside of the tires on each single axle, each tandem axle and each tridem axle is not less than 2.5 m and not more than 2.6 m.
 - (c) if the semi-trailer, pony trailer or full trailer was manufactured before January 1, 2008 and is equipped with super single tires, the distance across the outside of the tires on each single axle, each tandem axle and each tridem axle is not less than 2.3 m and not more than 2.6 m, and
 - (d) if the semi-trailer, pony trailer or full trailer was manufactured after December 31, 2007 and is equipped with super single tires, the distance across the outside of the tires on each single axle, each tandem axle and each tridem axle is not less than 2.5 m and not more than 2.6 m.

3 Section 7.08 (2) is amended

- (a) by repealing paragraph (c) and substituting the following:
 - (c) auxiliary equipment or devices that are not designed or used to carry cargo and do not extend more than 30 cm beyond the front or 10 cm beyond the rear of the vehicle, including, but not limited to, air connectors, electrical connectors, hydraulic connectors, rollers, pickup plates, bumpers, ladders, glad hands, load securement devices or dangerous goods placards;.

(b) by adding the following paragraph:

- (e) an aerodynamic device installed at the rear of the truck, trailer or semi-trailer if
 - (i) any portion of the device more than 1.9 m above the ground does not protrude more than 0.61 m beyond the rear of the vehicle,
 - (ii) any portion of the device within 1.9 m of the ground does not protrude more than 0.305 m beyond the rear of the vehicle, and
 - (iii) the aerodynamic device is not designed or used to carry cargo., and

(c) by repealing subsection (6) (b) (iii) and substituting the following:

(iii) auxiliary equipment or devices that are not designed or used to carry cargo and do not extend more than 30 cm beyond the front or 10 cm beyond the rear of the vehicle, including, but not limited to, air connectors, electrical connectors, hydraulic connectors, rollers, pickup plates, bumpers, ladders, glad hands, load securement devices or dangerous goods placards;